John Quaif
AI0112

Qualified RPII/PIPA

Tester for inflatables
and games.

## INSPECTION REPORT



Paul Quaif
AI0113
Qualified RPII/PIPA
Tester for inflatables
and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB

Email: paulquaif58@gmail.com

Website: www.pjentertainments.co.uk

	office:	0208 5	509 0150 Paul: 0796	66 375 570	Joh	n: 0796	6 375 57	1	
Company Name	NIT	AV	ENTERGAIN	Addross		000	0	500	
Televile and Miles		00		C-fortaut caa	`  -	COL	111/6	ERS	
				r' > -7		WE	TE	W W	
077	100		UNDAY LTD.	COF		716	TREE	COS ORH	
Serial No: 11	n 16	459		Date	of In	enastia		22 2:	
7			/			f Inspection: 22 – 05 – 24 te of Inspection: 21 – 65 – 25			
Inflatable Type:	GAME					21-05-25			
	77.1.10			Size (L x W x H) ( Manufacturer			n)	3.9 × 3.9 × 4.1	
Place of Inspection			1 4RE					TOP MAKERS INFO	MAD
. idee of mapeedon	- 10	K.Z.	TYKE	Date of	Ma.	nufactu	ıre	2018	
Structure			Anch	Orago					
Seams and webbing	1	/	Anchorage Condition of anchor points				Suitability Blower		
Bed panels and steps firm	N	A	Type of anchor poin		Ri	26		and outlet mesh	-
Walls and towers firm	1		Number of anchors	. 100	18	1		and plug	-
Grounding	NI	A	Anchor accessories		10		Impel		-
Sharp angles	1		Structural	Materials			Retur		-
Pressure (water gauge)	0	1	Zips				PAT to		
Entrapment	- 1		Ropes					r type/electric	-
Stability			Windows/netting					cover/casing	15
Deflation / evacuation time			Slic	les		-		se tested (PAT)	10
Air loss			Slide platform heigh	t (m)				r size (Hp)	0
Check toys/obstacles	N	Α	Height of walls (1st n					r tube length (m)	-7
Markings LAGEL	/\	/	Height of walls (m)	/				er of blowers (this unit)	77
Identification			Run Out (m)				Petrol blowers only (4hp)		
Art work (no significant peeling	g) N/	A	Clamber net/foam/la	addec				rea (L x W) (m)	_
Fall off height (m)	NI	A	Slide sheet					ber of users and user hei	ght
Open side fall off height (m)	NI	A	Totally Enclos	ed Structure	9			um user height (m)	.8
Step and ramp size (m)	_	Α	Exits and markings					um users at 1.0m	12
Internal wall height (m)	NI	A	Deflation of user are					um users at 1.2m	2
Stitching	V		Pressure or user area	1				um users at 1.5m	2
Trough depth	NA	-						um users at 1.8	2
Fabric (fire retardant)			INSPECTION RESULTS				Customise max user height		
Fabric (strength)	-		PASS		V			um users at customised	
Thread (non-rotting)	L.		FAIL				height		+

Notes/Risk Assessment:				
Notes/ Risk Assessment:	Signature of tester			
	Paul Quaif			
· · · · · · · · · · · · · · · · · · ·	John Quaif			

## Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit.

DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users.

I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report.

If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.

All anchor points must be used to secure the unit to the ground at all times.