

JOHN QUAIF  
RPII A1113  
PIPA 246

Qualified RPII / PIPA  
Tester for Inflatables  
and Games  
JOHNQUAIF@YAHOO.COM  
07966 375 571



PAUL QUAIF  
RPII A1112  
PIPA 264

Qualified RPII / PIPA  
Tester for Inflatables  
and Games  
PAULQUAIF58@GMAIL.COM  
07966 375 570

Company Name	funday	Address	creesy farm
Telephone No			Hutton
Email	office@funday LTD .com		CM13 1RZ

Serial No	P38535	Date of Inspection	16-6-2025
Name of Inspector	John Quaif	Expiry Date of Inspection	15-6-2026
Inflatable Type	Game	Size (L x W x H) (m)	7.9x8.6x2.5
Theme	Dash N grab	Manufacturer	AirQuee
Place of Inspection	Hutton	Date of Manufacture	2019

Structure	Anchorage	Blower
Seams and webbing	Condition of anchor points	Suitability
Bed panels and steps firm	Type of anchor point PVC Steel	Inlet and outlet mesh
Walls and towers firm	Number of anchors 15	Cable and plug
Grounding	Anchor accessories	Impeller
Sharp angles	Structural Materials	Return Flap
Pressure (KPA) 1.31	Zips 6	PAT test
Entrapment	Ropes	Blower type/electric
Stability	Windows/netting N/A	Motor cover/casing
Deflation/Evacuation time	Slides	Inhouse tested (PAT)
Air loss	Slide platform height (m)	Blower size (Hp) 1.5
Markings	Height of walls (1st m)	Blower tube length (m) 2.7
Identification	Height of walls (remainder)	Number of blowers (this unit) 1
Artwork (no significant peeling) N/A	Platform wall height (m)	Petrol blowers only N/A
Bed height (m)	Run out (m)	Play area (L x W) (m) 5.5x5.5
Open side fall off height (m) 600	Clamber net/foam/ladder	Number of users and user height
Step and ramp size (m) N/A	Slide sheet	Maximum user height (m) 1.8
Internal wall height (m) 1.9	Totally Enclosed Structure	Maximum users at 1.0m 0
Stitching	Exits and markings	Maximum users at 1.2m 4
Trough depth 50/500	Deflation of user area	Maximum users at 1.5m 4
Fabric (fire retardant)	Pressure or user area	Maximum users at 1.8m 4
Fabric (strength)	INSPECTION RESULTS	Customise max user height X
Thread (non-rotting)	PASS (P) V FAIL (F)	Maximum users at customised height X

Notes / Risk Assessment:	Signature of tester
must be attended at all times	Paul Quaif
	John Quaif

#### COMMENTS:

This unit must always be used with 2 inch thick, high density crash mats on all entrances and exits at a minimum of 1.2m from the unit. DO NOT operate in wind speeds in excess of 24mph/38kph. This unit must always be supervised by a competent adult who is capable of exercising authority over the users. I certify that the above equipment has been inspected to standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report. If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose. All anchor points must be used to secure the unit to the ground at all times.