

JOHN QUAIF

RPII A1113

PIPA 246

Qualified RPII / PIPA
Tester for Inflatables
and Games

JOHNQUAIF@YAHOO.COM

07966 375 571



15 LARKSWOOD ROAD, CHINGFORD, LONDON, E4 9DS

PAUL: 07966 375 570 JOHN: 07966 375 571

PAUL QUAIF

RPII A1112

PIPA 264

Qualified RPII / PIPA
Tester for Inflatables
and Games

PAULQUAIF58@GMAIL.COM

07966 375 570

Company Name	Funday Inflatable	Address	Coppingers House
Telephone No	079205 48548		West End
Email	office@funday LTD-com		CO5 0QH

Serial No	FD4650	Date of Inspection	15-7-2025
Name of Inspector	John Quaif	Expiry Date of Inspection	14-7-2026
Inflatable Type	Game	Size (L x W x H) (m)	2.7 x 5.6 x 5.0
Theme	Football Darts	Manufacturer	Better Bounce
Place of Inspection	CM13 1R2	Date of Manufacture	NOT KNOWN

Structure	Anchorage	Blower
Seams and webbing	Condition of anchor points	Suitability
Bed panels and steps firm	Type of anchor point	Inlet and outlet mesh
Walls and towers firm	Number of anchors	Cable and plug
Grounding	Anchor accessories	Impeller
Sharp angles	Structural Materials	Return Flap
Pressure (KPA)	Zips	PAT test
Entrapment	Ropes	Blower type/electric
Stability	Windows/netting	Motor cover/casing
Deflation/Evacuation time	Slides	Inhouse tested (PAT)
Air loss	Slide platform height (m)	Blower size (Hp)
Markings	Height of walls (1st m)	Blower tube length (m)
Identification	Height of walls (remainder)	Number of blowers (this unit)
Artwork (no significant peeling)	Platform wall height (m)	Petrol blowers only
Bed height (m)	Run out (m)	Play area (L x W) (m)
Open side fall off height (m)	Clamber net/foam/ladder	Number of users and user height
Step and ramp size (m)	Slide sheet	Maximum user height (m)
Internal wall height (m)	Totally Enclosed Structure	Maximum users at 1.0m
Stitching	Exits and markings	Maximum users at 1.2m
Trough depth	Deflation of user area	Maximum users at 1.5m
Fabric (fire retardant)	Pressure or user area	Maximum users at 1.8m
Fabric (strength)	INSPECTION RESULTS	Customise max user height
Thread (non-rotting)	PASS (P)	Maximum users at customised height
	FAIL (F)	

Notes / Risk Assessment:

Signature of tester

Paul Quaif

John Quaif

COMMENTS:

This unit must always be used with 2 inch thick, high density crash mats on all entrances and exits at a minimum of 1.2m from the unit. DO NOT operate in wind speeds in excess of 24mph/38kph. This unit must always be supervised by a competent adult who is capable of exercising authority over the users. I certify that the above equipment has been inspected to standards as indicated and complies with the current health and safety notes on inflatable play, BS EN14960 has been adopted where appropriate on the above inspection report. If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose. All anchor points must be used to secure the unit to the ground at all times.