John Quaif
AI0112
Qualified RPII/PIPA
Tester for inflatables
and games.

INSPECTION REPORT



Paul Quaif
AI0113
Qualified RPII/PIPA
Tester for inflatables
and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB

Email: paulquaif58@gmail.com

Website: www.pjentertainments.co.uk

Office: 0208 509 0150 Paul: 07966 375 570 John: 07966 375 571

		,							
Company Name FUNDAY &	3NT	ENTRIVIPENT	Address	5	colp	NIGO	EV2 S		
Telephone No 08700	,				WEST		00		
	OFFICE @ FUNDAY LTD. CON				TIPPREE COSORH				
1017112		2777 2111-60	, , ,		1111115		CO) CO(H		
Serial No: AQ 7430			Date	Date of Inspection: 22 - 05 - 24					
Name of Inspector: PAUL QUAIF		Expiry Date of Inspection			tion:	21-05-25			
Inflatable Type: GAINE			Size (L x W x H) (m))	12×5.17×1.75		
Theme HUMAN				nufa	cturer:		AIRQUEE		
	NR29 4RE		Date of Manufacture			re	2020		
THE THE									
Structure	Structure Ancho						Blower		
scams and webbing	Condition of anchor		points		~	Suital	oility		1
	4	Type of anchor poin	it WEB	RIK	G	Inlet and outlet mesh			~
Walls and towers firm		Number of anchors		12		Cable and plug			
Grounding N/	4	Anchor accessories			-	Impeller			
Sharp angles	4	Structura	Materials		Ret		n flap		-
Pressure (water gauge) 4.8 4	4	Zips	4		-	PAT to	est		/
Entrapment 1		Ropes	'	N	A	Blower type/electric		-	
Stability		Windows/netting		. /	V	Motor cover/casing			/
Deflation / evacuation time Slid			des			Inhou	se tested (PAT)		1
Air loss 1		Slide platform heigh	nt (m)				er size (Hp)	1.5	~
Check toys/obstacles	A,	Height of walls (1st n)				Blower tube length (m)			4
Markings LABEL 1		Height of walls (m)				Numb	er of blowers (this unit)		1
Identification		Run Out (m)				Petro	blowers only (4hp)	-	-
Art work (no significant peeling) N//	4	Clamber net/foam/	ladder			Play A	rea (L x W) (m)	_	-
Fall off height (m)		Slide sheet				Nur	nber of users and user h	eigh	nt
Open side fall off height (m) N		Totally Enclo	sed Structu	re		Maxir	num user height (m)	1.8	3
Step and ramp size (m) N) / F	4	Exits and markings				Maximum users at 1.0m			10
Internal wall height (m)	0	Deflation of user a	ęa			Maxir	num users at 1.2m		10
Stitching		Pressure or user are	;a\			Maxir	num users at 1.5m		10
Trough depth N/	7				Maxir	num users at 1.8		10	
Fabric (fire retardant)		INSPECTION RESULTS				Custo	mise max user height	-	
r district fact entBerry		PASS		t		Maxir	num users at customise	d	
Thread (non-rotting)	4	FAIL				heigh	t ==		

Notes/	'Risk	Assessment:
--------	-------	-------------

Paul Quaif

John Quaif

Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit.

DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users.

I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report.

If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.

All anchor points must be used to secure the unit to the ground at all times.