John Quaif
AI0112
Qualified RPII/PIPA
Tester for inflatables
and games.

INSPECTION REPORT



Paul Quaif
AI0113
Qualified RPII/PIPA
Tester for inflatables
and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB

Email: paulquaif58@gmail.com

Website: www.pjentertainments.co.uk

Office: 0208 509 0150 Paul: 07966 37

Paul: 07966 375 570 John: 07966 375 571

Company Name GUDDAY PK				0		
1 00 1751-7 -1-0	TERTAINMENT	Address	COL	PINGERS		
Telephone No 08700	113993		WE	TEND RD		
Email DERICE D	EUNDAY LTD. (m	TIPT	RE COS DQH		
Serial No: FDE 00115		Date o	of Inspection	on: 22-05-24		
Name of Inspector: PAUL QUAIF		Expiry Da	te of Inspe	ction: 21 - 05 - 25		
Inflatable Type: GrAynE		Size (L	x W x H) (m) 4.1 x 2.8 x 3.65		
Theme SPEED CA	ACK FOOTBALL	Manufacturer:		BOING		
Place of Inspection 10 10	29 4RE			ure NOT KNOWN		
	1 100			1501 (51555)		
Structure		norage		Blower		
Seams and webbing	Condition of ancho	r points	1/	Suitability 1		
Bed panels and steps firm NIA		Type of anchor point WEB RING		Inlet and outlet mesh		
Walls and towers firm	Number of anchors	Number of anchors 6		Cable and plug		
Grounding N/A		Anchor accessories		Impeller L		
Sharp angles		Structural Materials		Return flap &		
Pressure (water gauge) 5./	Zips		NA	PAT test		
Entrapment	_	Ropes		Blower type/electric		
Stability		Windows/netting		Motor cover/casing		
Deflation / evacuation time		Slides		Inhouse tested (PAT)		
Air loss		Slide platform height (m)		Blower size (Hp)) . 5"		
Check toys/obstacles N/A		Height of walls (1st m)		Blower tube length (m)) · 3		
Markings HAND-WRITTEN	Height of walls (m)			Number of blowers (this unit)		
Identification		Run Out (m)		Petrol blowers only (4hp)		
Art work (no significant peeling)		Clamber net/foam/ladder		Play Area (L x W) (m)		
Fall off height (m) NA		Slide sheet		Number of users and user height		
Open side fall off height (m) № 1/A		Totally Enclosed Structure		Maximum user height (m)		
Step and ramp size (m) NA	Exits and markings			Maximum users at 1.0m		
Internal wall height (m) (N) (1) (E)	Deflation of user ar	~		Maximum users at 1.2m		
Stitching	Pressure or user ar	ea		Maximum users at 1.5m 1		
Trough depth NA	10100000000			Maximum users at 1.8		
Fabric (fire retardant)		INSPECTION RESULTS		Customise max user height		
Fabric (strength)	PASS		1	Maximum users at customised		
Thread (non-rotting)	FAIL			height		
Notes/Risk Assessment: Signature of tester/						
Notes/ Risk Assessment:			Paul Quaif			

Paul Quait	(Kin
John Quaif	/

Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit.

DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users.

I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report.

If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.