John Quaif Tester for inflatables and games.

INSPECTION REPORT



Paul Quaif Qualified RPII/PIPA and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB Email: paulquaif58@gmail.com

Website: www.pjentertainments.co.uk

	Office	: 0208 50	09 0150 Paul: 0796	66 375 570	John: 0796	6 375 57	1		
Company Name	FUNDO	W PI	JERTAINMENT	Addres	2	enPP	NGERS		
Telephone No	0820	0	113 993	5	WE		NGEIL)		
Email	OPP	E 6	FINDAY LTD	-Cam		THEE	COT DOW		
	OFFIC	-	TVOURY -19	COM	111	THEE	COS ORH		
Serial No: FD OD			Date of Inspection			n:	29-05-24		
Name of Inspector: PAIL				iry Date of Inspection:		28 - 05 - 25			
Inflatable Type:	Ba	AME	Color		L x W x H) (r				
Theme	-		SLIDE BED ON				100000		
Place of Inspection	N	R29	UNE BUYONG		of Manufact		NOT KNOWN		
		112/	414	Date of Manufacture NOT			NOT KNOWN		
Structure			Anchorage				Blower		
Seams and webbing			Condition of anchor points			Suitability			
Bed panels and steps firm			Type of anchor poin	nt PVC W	BB RING V		nd outlet mesh	-	
Walls and towers firm			Number of anchors		8		and plug	-	
Grounding 85 KG			Anchor accessories			Impeller			
Sharp angles			Structural Materials			Return flap			
Pressure (water gauge)	4.2		Zips		41	PAT to	st	-	
Entrapment			Ropes		NIA	Blowe	r type/electric	v	
Stability			Windows/netting NA		Motor cover/casing ~				
Deflation / evacuation time			Slides			Inhous	se tested (PAT)		
Air loss			Slide platform height (m)			Blower size (Hp)			
Check toys/obstacles NA			Height of walls (1 st m)			Blower tube length (m) 1 · 2			
Markings LABEL V			Height of walls (m)			Number of blowers (this unit)			
Identification)			Run Out (m)			Petrol blowers only (4hp)			
Art work (no significant peeling)			Clamber net/foam/ladder			Play Area (L x W) (m)			
Fall off height (m) 0 · 63			Slide sheet			Number of users and user height			
Open side fall off height (m) 0 · 63		Totally Enclosed Structure			Maximum user height (m) 1.2				
Step and ramp size (m)	N	A	Exits and markings				ium users at 1.0m	2	
Internal wall height (m) Stitching	- 0	6	Deflation of user are				um users at 1.2m	2	
Trough depth			Pressure or user are	a \			um users at 1.5m	\times	
Fabric (fire retardant)						Maximum users at 1.8			
Fabric (strength)		INSPECTION RESULTS			Customise max user height				
Thread (non-rotting)		-	PASS				um users at customised	V	
			FAIL			height		$\perp \wedge$	
Notes/Risk Assessme	nt: As i	NATE	M 15 VSED. TH	tis itter HILST	N MUST IN USE.	Paul (Signature of tester	_	

John Quaif

Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit. DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users. I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report. If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.

All anchor points must be used to secure the unit to the ground at all times.